

Conversion degrés/minute (x°xx') en millimètres (mm)

**Conversion degré/minute (x°xx') en millimètre (mm)**

Degré/minute	DIAMETRE NOMINAL DE LA JANTE (Pouce)									
	10"	12"	13"	14"	15"	16"	17"	18"	19"	20"
0°01'	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm
0°02'	0.1 mm	0.2 mm	0.2 mm	0.2 mm	0.2 mm	0.2 mm	0.3 mm	0.3 mm	0.3 mm	0.3 mm
0°03'	0.2 mm	0.3 mm	0.3 mm	0.3 mm	0.3 mm	0.4 mm	0.4 mm	0.4 mm	0.4 mm	0.4 mm
0°04'	0.3 mm	0.4 mm	0.4 mm	0.4 mm	0.4 mm	0.5 mm	0.5 mm	0.5 mm	0.6 mm	0.6 mm
0°05'	0.4 mm	0.5 mm	0.5 mm	0.5 mm	0.6 mm	0.6 mm	0.7 mm	0.7 mm	0.7 mm	0.7 mm
0°06'	0.4 mm	0.5 mm	0.6 mm	0.6 mm	0.7 mm	0.7 mm	0.8 mm	0.8 mm	0.8 mm	0.9 mm
0°07'	0.5 mm	0.6 mm	0.7 mm	0.7 mm	0.8 mm	0.8 mm	0.9 mm	0.9 mm	1 mm	1 mm
0°08'	0.6 mm	0.7 mm	0.8 mm	0.8 mm	0.9 mm	1 mm	1 mm	1.1 mm	1.1 mm	1.2 mm
0°09'	0.6 mm	0.8 mm	0.9 mm	0.9 mm	1 mm	1.1 mm	1.2 mm	1.2 mm	1.3 mm	1.3 mm
0°10'	0.7 mm	0.9 mm	1 mm	1 mm	1.1 mm	1.2 mm	1.3 mm	1.3 mm	1.4 mm	1.5 mm
0°11'	0.8 mm	1 mm	1.1 mm	1.1 mm	1.2 mm	1.3 mm	1.4 mm	1.5 mm	1.5 mm	1.6 mm
0°12'	0.9 mm	1.1 mm	1.2 mm	1.2 mm	1.3 mm	1.4 mm	1.6 mm	1.6 mm	1.7 mm	1.8 mm
0°13'	1 mm	1.2 mm	1.3 mm	1.3 mm	1.4 mm	1.6 mm	1.7 mm	1.7 mm	1.8 mm	1.9 mm
0°14'	1 mm	1.3 mm	1.4 mm	1.4 mm	1.5 mm	1.7 mm	1.8 mm	1.8 mm	2 mm	2.1 mm
0°15'	1.1 mm	1.4 mm	1.5 mm	1.6 mm	1.7 mm	1.8 mm	2 mm	2 mm	2.1 mm	2.2 mm
0°16'	1.1 mm	1.5 mm	1.6 mm	1.6 mm	1.8 mm	1.9 mm	2.1 mm	2.1 mm	2.2 mm	2.3 mm
0°17'	1.2 mm	1.5 mm	1.7 mm	1.7 mm	1.9 mm	2 mm	2.2 mm	2.3 mm	2.4 mm	2.5 mm
0°18'	1.3 mm	1.6 mm	1.8 mm	1.8 mm	2 mm	2.2 mm	2.3 mm	2.4 mm	2.5 mm	2.6 mm
0°19'	1.3 mm	1.7 mm	1.9 mm	1.9 mm	2.1 mm	2.3 mm	2.5 mm	2.5 mm	2.7 mm	2.8 mm
0°20'	1.4 mm	1.8 mm	2 mm	2.1 mm	2.2 mm	2.4 mm	2.6 mm	2.7 mm	2.8 mm	2.9 mm
0°21'	1.5 mm	1.9 mm	2.1 mm	2.2 mm	2.3 mm	2.5 mm	2.7 mm	2.8 mm	2.9 mm	3.1 mm
0°22'	1.5 mm	2 mm	2.2 mm	2.3 mm	2.4 mm	2.6 mm	2.9 mm	2.9 mm	3.1 mm	3.2 mm
0°23'	1.7 mm	2.1 mm	2.3 mm	2.4 mm	2.5 mm	2.8 mm	3 mm	3 mm	3.2 mm	3.4 mm
0°24'	1.8 mm	2.2 mm	2.4 mm	2.5 mm	2.8 mm	2.9 mm	3.1 mm	3.2 mm	3.4 mm	3.5 mm
0°25'	1.8 mm	2.3 mm	2.5 mm	2.6 mm	2.8 mm	3 mm	3.3 mm	3.3 mm	3.5 mm	3.7 mm
0°26'	1.9 mm	2.3 mm	2.6 mm	2.7 mm	2.9 mm	3.1 mm	3.4 mm	3.5 mm	3.6 mm	3.8 mm
0°27'	2 mm	2.4 mm	2.7 mm	2.8 mm	3 mm	3.2 mm	3.5 mm	3.6 mm	3.8 mm	4 mm
0°28'	2 mm	2.5 mm	2.8 mm	2.9 mm	3.1 mm	3.4 mm	3.6 mm	3.7 mm	3.9 mm	4.1 mm
0°29'	2.1 mm	2.6 mm	2.9 mm	3.1 mm	3.2 mm	3.5 mm	3.8 mm	3.9 mm	4.1 mm	4.3 mm
0°30'	2.1 mm	2.7 mm	3 mm	3.1 mm	3.3 mm	3.6 mm	3.8 mm	4 mm	4.2 mm	4.4 mm
0°35'	2.5 mm	3.2 mm	3.5 mm	3.6 mm	3.9 mm	4.2 mm	4.5 mm	4.6 mm	4.9 mm	5.1 mm
0°40'	2.8 mm	3.6 mm	4 mm	4.1 mm	4.4 mm	4.8 mm	5 mm	5.1 mm	5.6 mm	5.9 mm
0°45'	3.2 mm	4.1 mm	4.5 mm	4.6 mm	5 mm	5.4 mm	5.8 mm	6 mm	6.3 mm	6.6 mm
0°50'	3.7 mm	4.5 mm	5 mm	5.2 mm	5.5 mm	6 mm	6.4 mm	6.7 mm	7.0 mm	7.3 mm
0°55'	4 mm	5 mm	5.5 mm	5.8 mm	6.1 mm	6.6 mm	7.1 mm	7.3 mm	7.7 mm	8.1 mm
1°00'	4.3 mm	5.4 mm	5.8 mm	6 mm	6.6 mm	7.1 mm	7.5 mm	8 mm	8.4 mm	8.8 mm

Exemple: 10 minutes pour une jante de 14" = 1 millimètre

1 degré = 60 min donc 6 mm

